

# DryDock<sup>®</sup> Seal System

## DOCK SEAL SPECIFICATIONS

MODEL S 900



### Design Highlights

- Protects Dock from Moisture Infiltration, Keeping Products Safe from Costly Water Damage
- Automatic Position, No Manual Activation Necessary
- Heavy-duty Galvanized Steel Channel Head Frame  
Translucent Fiberglass Raked Head Frame for Fast Water Drainage
- High-resilient Foam Core Protected by Three Layers Of Durable Coated Fabric
- Seal Easily Replaceable, Reducing Down Time and Maintenance Costs
- Rugged Support Brackets for Mounting Over Existing Equipment
- Weighted Side Covers Provide Extra Protection for The Dock Area (Not Shown)
- Covers Trucks 12"-9' to 13'-6" High



### Project Information

Job Name \_\_\_\_\_  
Address \_\_\_\_\_  
General Contractor \_\_\_\_\_  
Distributor \_\_\_\_\_  
Model \_\_\_\_\_ Quantity \_\_\_\_\_

### Certified For Construction

By \_\_\_\_\_  
Company \_\_\_\_\_  
Address \_\_\_\_\_  
Date \_\_\_\_\_



# DryDock<sup>®</sup> Seal System

## DOCK SEAL SPECIFICATIONS

MODEL S 900

### APPLICATION DATA

Door Width: \_\_\_\_\_ ft. \_\_\_\_\_ in.

Door Height: \_\_\_\_\_ ft. \_\_\_\_\_ in.

Dock Height: \_\_\_\_\_ ft. \_\_\_\_\_ in.

Bumper Protection\*: \_\_\_\_\_ in.

(\*Includes bumper projection and any building wall/foundation offset or cantilever)

### TRUCKS AND TRAILERS SERVICED

Width: \_\_\_\_\_ Max. \_\_\_\_\_ Min.

Height: \_\_\_\_\_ Max. \_\_\_\_\_ Min.

Length: \_\_\_\_\_ Max. \_\_\_\_\_ Min.

Hydraulic Tailgate:  Yes  No

Rear Step Section:  Yes  No

Tailgate/Step Section Size: \_\_\_\_\_ In.

Yard Jockeys:  Yes  No

### QUANTITY \_\_\_\_\_

**Drive/Approach**  Level  Incline  Decline \_\_\_\_\_ % Grade

**Weighted Side Covers:** 22 oz. Vinyl

**Color**  Black  Tan  Brown  Blue  Green  
 Flame Retardant Fabric and Foam  Flame Retardant Fabric Only

**Removable Cover Material:** XL-100™

**Color**  Black  Tan  Brown  Blue  Green

**Wear Pleat Material:** XL-100™

**Color**  Black  Tan  Brown  Blue  Green  
 Flame Retardant Fabric and Foam  Flame Retardant Fabric Only

**Head Frame Material:** Galvanized Steel

**Top Projection of Dock Seal:** \_\_\_\_\_

**DryDock Headframe Projection:** \_\_\_\_\_ (18" greater than dock seal top projection)

**Dock Seal Overall Unit Height Off Grade at Wall**

**Dock Seal Unit Width** \_\_\_\_\_ (total inches)

**Dock Seal Unit Width Including Mounting Brackets**

**DryDock Head Frame Width** \_\_\_\_\_ (total Inches)

**Building Wall Construction:**  Metal  Other

\*Conversions: To convert measurements to metric, see formulas below:

Inches x 25.4 = millimeters (Example: 4" x 25.4 = 101.6 mm)

Feet x .3048 = meters (Example: 12' x .3048 = 3.66 m)

\*Note: Consult factory for blackout application assistance.

