



SI-350 Inflatable Dock Seal®

SEAL AND SHELTER SPECIFICATIONS

MODEL SI 350

The Serco SI-350 is designed for sloped drive conditions for doors up to 8' wide and 10' high and is ideal for prefabricated buildings where excessive wall pressure could damage the building structure.

In sloped drive conditions, the slightly tapered vertical seals form a seal parallel to the sides of the trailer while the adjustable header inflates to seal the trailer top.

Design Highlights

- Tight, Energy-efficient Seal
- Minimal Pressure to the Building Wall
- Full-width Adjustable Header Seal
- Choice of Fabric and Colors



Project Information

Job Name _____

Address _____

General Contractor _____

Distributor _____

Quantity _____

Voltage _____ Phase _____

Certified For Construction

By _____

Company _____

Address _____

Date _____



SI-350 Inflatable Dock Seal®

SEAL AND SHELTER SPECIFICATIONS

MODEL SI 350

APPLICATION INFORMATION:

Standard unit size 9'-4" W x 11'-8" H to fit door openings 8' W x 10' H or smaller. Bottom of head frame to be minimum of 15' off ground. Minimum projection beyond bumpers 6".

Front opening is 7'-6" W and header curtain has drop of 48". On a 48" dock height this would service trailers 11' to 13'-6" H.

Wiring from 110 power source to switch and from switch to motor/blower

by others.

If other than standard unit required consult factory.

DETAILS:

Quantity _____

Door opening _____ Dock Height _____

Unit size _____ W x _____ H x _____ Proj.

Truck Coverage (off ground) _____ to _____

Approach Level _____ Incline _____

Decline _____ Percentage _____

Difference in 50' _____

NOTE: Maximum % of slope without tapering shelter frame is 3%.

CURTAIN MATERIAL:

- 16 oz. Hypalon® - Black 16 oz. Hypalon® - Blue 16 oz. Hypalon® - Green
- 16 oz. Hypalon® - Brown 16 oz. Hypalon® - Tan
- 14 oz. Polyurethane - Black
- 9 oz. Vinyl - Tan

SPECIAL INFORMATION SPECIFY:

